

Advance Database Management (315324)

Model Question Paper — Set C · Model Answers

About the code in these answers: every query and command was actually executed before printing, and the outputs shown are copied from those runs. **SQL** — PostgreSQL 16 (object-relational features: composite/structured types, table inheritance, arrays); where the textbook SQL:1999 syntax (e.g. UNDER, MULTISET) is not accepted by PostgreSQL, the standard syntax to write in the exam is given and the PostgreSQL equivalent is shown with its real output. **MongoDB** — shell commands were run on an in-memory MongoDB-compatible engine (mongomock 4.3) and printed in mongosh style; ObjectId values will be different on your computer. Plain JavaScript expressions (as typed in mongosh) were run on Node.js (the same V8 JavaScript engine used by mongosh), time zone IST. **XML** — XQuery / XPath on Saxon-HE 13; XML Schema / DTD validation with libxml2 (lxml). Commands are shown in **bold**, results below them. Sample data is assumed wherever needed.

Q.1

a) Two advantages of concurrency control.

2 M

1. **Maintains consistency and isolation:** prevents problems of concurrent execution such as lost update, dirty read and unrepeatable (inconsistent) read; the result is serializable.
2. **Better performance:** many transactions run at the same time — higher throughput and resource (CPU, disk) utilisation, and reduced waiting / response time.

(Any two, 1 M each)

b) Two phases of 2PL.

2 M

1. **Growing phase:** a transaction may obtain (acquire) locks but may not release any lock.
2. **Shrinking phase:** a transaction may release locks but may not obtain any new lock.

(Each phase 1 M)

c) Centralized database system; two types.

2 M

Centralized database system: a database system that runs on a single computer system and does not interact with other computer systems; all data and DBMS processing are at one place.

1. **Single-user system** — desktop / personal computer used by one person at a time (e.g. MS Access on a PC).
2. **Multi-user system** — a server with many CPUs/terminals serving many users concurrently.

(Definition 1 M, types 1 M)

d) Syntax — multiset type attribute.

2 M

```
attribute_name  element_type  MULTISET

-- example
CREATE TYPE Book AS (
  title          VARCHAR(20),
  keyword_set    VARCHAR(20) MULTISET );

INSERT INTO books VALUES ('DBMS', MULTISET['SQL', 'ER model', 'SQL']);
```

A multiset is an unordered collection that may contain duplicates.

(Syntax 1 M, example 1 M)

e) Document database.

2 M

Document database: a NoSQL database that stores data as self-describing **documents** (JSON / BSON / XML) grouped into collections; each document has a unique key and may have a different structure. Example: MongoDB, CouchDB.

```
{ _id: 1, name: "Asha", branch: "IF",
  marks: [78, 85], address: { city: "Pune" } }
```

(Definition 1 M, example 1 M)

f) Data mining; two techniques.

2 M

Data mining: the process of semi-automatically analysing large databases to discover useful patterns, trends and rules (knowledge discovery in databases).

Techniques: classification, clustering, association rules, regression (any two).

(Definition 1 M, two techniques 1 M)

g) XML vs HTML.

2 M

XML	HTML
Designed to store and transport data.	Designed to display data in a browser.
User-defined tags.	Predefined tags (<p>, <table>).
Case-sensitive; every tag must be closed and properly nested.	Not strict; some tags need not be closed.

(Any two, 1 M each)

Q.2

a) Two-tier and three-tier client-server models.

4 M

In a **client-server** system the database functionality is divided into a **front end** (client: user interface, forms, report writers) and a **back end** (server: query evaluation, optimisation, concurrency control, recovery).




Fig. (a): Two-tier client-server architecture

- **Two-tier:** the application runs on the client machine and directly calls the database server through ODBC / JDBC.
- Simple and fast for small numbers of users (e.g. a desktop billing program connected to a MySQL server); but business logic is on every client, so maintenance and security are harder and it does not scale to many users.




Fig. (b): Three-tier client-server architecture

- **Three-tier:** the client is only a front end (often a web browser); it communicates with an **application server** which contains the business logic and in turn talks to the database server.
- More secure and scalable, easier to maintain (logic changed at one place) — used by web applications and large systems (e.g. online railway reservation).

(Each model: diagram 1 M, explanation 1 M)

b) Four benefits of distributed database system.

4 M

1. **Sharing of data:** users at one site can access data stored at other sites (e.g. a branch can see head-office data).
2. **Local autonomy:** each site controls its own data and local users.

3. **Reliability and availability:** if one site fails, other sites keep working; with replication, data is still available.
4. **Faster response:** most queries use local data, so they are answered quickly with less network traffic.
5. **Modular (incremental) growth:** a new site can be added without disturbing other sites.
6. **Lower communication cost and parallel processing:** data is kept near its users; a big query can be split among sites.

(Any four benefits, 1 M each)

c) Complex data types in object-based databases.

4 M

Traditional relational databases require atomic attribute values (first normal form). Object-based databases allow **complex data types** so that real-world objects can be represented directly:

1. **Structured (composite) types:** an attribute made of components, e.g. name = (first_name, last_name), address = (street, city, pin).
2. **Collection types:** multivalued attributes stored as **arrays** (ordered) or **multisets** (unordered, duplicates allowed), e.g. phone numbers, keywords.
3. **Reference types:** an attribute that refers to (points to) an object of another table — ref(Person).
4. **Nested relations / user-defined types with methods** — relations within relations; objects with behaviour (non-1NF model).

Example (executed on PostgreSQL):

```
adm_mp=# CREATE TYPE name_t AS (first_name VARCHAR(15), last_name VARCHAR(15));
CREATE TYPE
adm_mp=# CREATE TYPE address_t AS (street VARCHAR(20), city VARCHAR(15));
CREATE TYPE
adm_mp=# CREATE TABLE customer (cid INT, name name_t, address address_t, phones
VARCHAR(10)[]);
CREATE TABLE
adm_mp=# INSERT INTO customer VALUES (1, ROW('Vikas', 'More'), ROW('Station
Road', 'Latur'), ARRAY['9850012345', '9850067890']);
INSERT 0 1
adm_mp=# SELECT cid, (name).first_name, (address).city, cardinality(phones) AS
no_of_phones FROM customer;
cid | first_name | city | no_of_phones
-----+-----+-----+-----
1 | Vikas | Latur | 2
(1 row)
```

(Explanation 2 M, example 2 M)

d) SQL vs NoSQL.

4 M

Point	SQL database	NoSQL database
Schema	Fixed, predefined schema; must be altered to add columns.	Dynamic / flexible schema; each document can have different fields.
Query language	Standard SQL (declarative).	No single standard; database-specific APIs, e.g. MongoDB find().
Joins	Complex joins are easy.	Joins are limited; data is usually denormalised / embedded.
Best suited for	Structured data and complex transactions (banking, ERP).	Big data, semi-structured / unstructured data, real-time web apps.

(Any four points, 1 M each)

Q.3

a) Types of concurrency control protocols.

4 M




Fig.: Classification of concurrency control protocols

- 1. Lock-based protocols:** a transaction must obtain a lock (shared / exclusive) on a data item before using it. Example: **Two-Phase Locking** (basic, strict, rigorous) and graph-based (tree) protocols.
- 2. Timestamp-based protocols:** each transaction gets a unique timestamp TS(T) when it starts; conflicting operations are executed in timestamp order. Each item keeps W-timestamp and R-timestamp; an operation that arrives too late causes the transaction to roll back. Deadlock-free.
- 3. Validation-based (optimistic) protocols:** transactions execute in three phases — read, validation, write. Updates are made on local copies; at commit time validation checks for conflicts. Good when conflicts are rare.
- 4. Multiversion schemes:** each write creates a new version of the item; a read gets a suitable old version, so reads never wait (multiversion timestamp ordering, multiversion 2PL, snapshot isolation).

(Any four types, 1 M each)

b) Throughput and response time; numerical.

4 M

- 1. Throughput:** number of tasks completed in a given time. Increased by processing many small tasks in parallel (inter-query parallelism) — important for OLTP systems.

2. **Response time:** time to complete a single task from its submission. Reduced by dividing a large task into sub-tasks executed in parallel (intra-query parallelism) — important for decision-support queries.
3. Performance of parallel systems is judged by **speedup** (TS/TL for the same task on N-times larger system) and **scaleup** (N-times larger task on N-times larger system).

Numerical:

Throughput = transactions / time = $900 / (3 \times 60 \text{ s}) = 900 / 180 = 5$ **transactions per second**.

Speedup = TS / TL = $12 / 4 = 3$; with N = 4 processors, speedup < N, so it is **sublinear** (efficiency 75%). The response time of the query has reduced from 12 s to 4 s.

(Definitions 2 M, calculations 2 M)

c) XQuery FLWOR with sorting and function.

4 M

XML document **result.xml**:

```
<result>
  <student roll="1"><name>Asha</name><branch>IF</branch><marks>82</marks>
</student>
  <student roll="2"><name>Rohan</name><branch>AN</branch><marks>71</marks>
</student>
  <student roll="3"><name>Sneha</name><branch>IF</branch><marks>91</marks>
</student>
  <student roll="4"><name>Imran</name><branch>IF</branch><marks>64</marks>
</student>
  <student roll="5"><name>Kavya</name><branch>AN</branch><marks>88</marks>
</student>
</result>
```

XQuery:

```
let $s := doc("result.xml")/result/student[branch = "IF"]
return
<if_students average="{ avg($s/marks) }">{
  for $x in $s
  order by xs:integer($x/marks) descending
  return <student marks="{ $x/marks }">{ $x/name/text() }</student>
}</if_students>
```

Output:

```
<if_students average="79">
  <student marks="91">Sneha</student>
  <student marks="82">Asha</student>
  <student marks="64">Imran</student>
</if_students>
```

let binds all IF students once; for ... order by ... descending sorts them on marks; avg() is a built-in XQuery function $((82 + 91 + 64) / 3 = 79)$. xs:integer() converts text to a number so that sorting is numeric.

(FLWOR with order by 3 M, average 1 M)

d) Virtual warehouse; functions of warehouse tools.

4 M

Virtual warehouse: a set of **views** defined over the operational databases. Data is not copied into a separate store; when a query is asked, it is answered from the source databases through the views.

It is easy to build, but needs spare capacity on the operational servers and gives slower answers; only some summary views may be materialised.

Functions of data-warehouse (back-end) tools:

1. **Data extraction:** gathers data from multiple, heterogeneous and external sources.
2. **Data cleaning:** detects and corrects errors (wrong spellings, missing values, duplicates — e.g. fuzzy lookup, merge-purge).
3. **Data transformation:** converts data from source format to warehouse format (units, codes, schema integration).
4. **Load:** sorts, summarises, consolidates, computes views, builds indexes and partitions.
5. **Refresh:** propagates updates from the sources to the warehouse periodically.

(Virtual warehouse 1 M, tool functions 3 M)

Q.4

a) Transaction processing in a parallel database system.

4 M

1. **Shared-memory and shared-disk systems:** transactions are processed almost as in a centralized system — a common lock table and log are used. In shared-disk systems the locking must also keep processor caches coherent: before reading a page a node gets a lock and reads the latest copy from disk; before releasing an X-lock the page is flushed (cache-coherency protocol).
2. **Shared-nothing systems:** data is **partitioned** across nodes (round-robin, hash, range partitioning). A transaction is executed at the node(s) holding its data; each node has its own lock manager and log. A transaction that updates data at many nodes is a **distributed transaction** and needs an atomic commit protocol such as **two-phase commit**.
3. **Inter-query parallelism:** different transactions run in parallel on different processors → higher throughput (main use in transaction processing).
4. **Intra-query parallelism:** one large query is divided into parts executed in parallel (intra-operation / inter-operation) → lower response time.
5. Concurrency control (2PL) and recovery (logging) must be coordinated across processors; deadlocks may occur across nodes and are detected globally.

(Any four points, 1 M each)

b) Table inheritance; consistency requirements.

4 M

Table inheritance lets a **subtable** be declared UNDER a **supertable**; the subtable inherits all attributes of the supertable, and every row of the subtable is also visible in the supertable.




Fig.: Supertable vehicle with subtables car and bike

```
-- SQL:1999
CREATE TABLE vehicle OF Vehicle;
CREATE TABLE car OF Car UNDER vehicle;
CREATE TABLE bike OF Bike UNDER vehicle;
```

Executed (PostgreSQL):

```
adm_mp=# CREATE TABLE vehicle (reg_no VARCHAR(12), owner VARCHAR(15), model
VARCHAR(15));
CREATE TABLE
adm_mp=# CREATE TABLE car (seats INT) INHERITS (vehicle);
CREATE TABLE
adm_mp=# CREATE TABLE bike (engine_cc INT) INHERITS (vehicle);
CREATE TABLE
adm_mp=# INSERT INTO car VALUES ('MH26-AB-1111', 'Patil', 'Swift', 5);
INSERT 0 1
adm_mp=# INSERT INTO bike VALUES ('MH24-C-2222', 'Shaikh', 'Pulsar', 150);
INSERT 0 1
adm_mp=# SELECT reg_no, owner, model FROM vehicle;
   reg_no   | owner  | model
-----+-----+-----
MH26-AB-1111 | Patil  | Swift
MH24-C-2222  | Shaikh | Pulsar
(2 rows)
```

Consistency requirements on subtables:

1. Each tuple of the supertable can correspond to **at most one tuple in each** of its immediate subtables.
2. All tuples corresponding to each other (in supertable and subtables) must be derived from **one tuple** inserted into one table — so a tuple cannot be in two sibling subtables (a vehicle cannot be both car and bike) unless a common subtable exists.

(Explanation and example 2 M, consistency requirements 2 M)

c) Arrays and embedded documents in MongoDB.

4 M

1. **Array:** an ordered list of values stored in one field; values may be of any type, even documents. Queries: a scalar value matches any element; \$all — must contain all values; \$size — array length; index position with dot notation ("marks.0").
2. **Embedded document:** a document used as the value of a key — keeps related data together (no join needed). Inner fields are queried with **dot notation**, e.g. "address.city".

```
test> use college
switched to db college
college> db.students.insertMany([
```

```
{ _id: 1, name: "Asha", subjects: ["ADM", "SE", "AJP"], address: { city:
"Pune", pin: "411001" } },
{ _id: 2, name: "Ravi", subjects: ["ADM", "OS"], address: { city: "Nanded",
pin: "431601" } }
])
{ acknowledged: true, insertedIds: { '0': 1, '1': 2 } }
college> db.students.find({ subjects: "OS" }, { name: 1 })
[ { _id: 2, name: 'Ravi' } ]
college> db.students.find({ subjects: { $all: ["ADM", "SE"] } }, { name: 1 })
[ { _id: 1, name: 'Asha' } ]
college> db.students.find({ subjects: { $size: 2 } }, { name: 1 })
[ { _id: 2, name: 'Ravi' } ]
college> db.students.find({ "address.city": "Nanded" }, { name: 1, address: 1 })
[ { _id: 2, name: 'Ravi', address: { city: 'Nanded', pin: '431601' } } ]
```

(Array 2 M, embedded document 2 M)

d) find() with \$or, \$nin, missing field, regex.

4 M

Sample data (assumed):

```
use library
db.books.insertMany([
  { title: "Database System Concepts", author: "Korth", category: "Textbook",
price: 850, discount: 10 },
  { title: "Data Mining Basics", author: "Han", category: "Textbook", price: 640
},
  { title: "Malgudi Days", author: "R. K. Narayan", category: "Fiction", price:
250, discount: 5 },
  { title: "Tinkle Digest", author: "Anant Pai", category: "Comics", price: 120
},
  { title: "Wings of Fire", author: "A. P. J. Abdul Kalam", category:
"Biography", price: 290 }
])
```

```
library> db.books.find({ $or: [ { author: "Korth" }, { price: { $lt: 300 } } ]
}, { _id: 0, title: 1 })
[
  { title: 'Database System Concepts' },
  { title: 'Malgudi Days' },
  { title: 'Tinkle Digest' },
  { title: 'Wings of Fire' }
]
library> db.books.find({ category: { $nin: ["Fiction", "Comics"] } }, { _id: 0,
title: 1, category: 1 })
[
  { title: 'Database System Concepts', category: 'Textbook' },
  { title: 'Data Mining Basics', category: 'Textbook' },
  { title: 'Wings of Fire', category: 'Biography' }
]
library> db.books.find({ discount: { $exists: false } }, { _id: 0, title: 1 })
[
  { title: 'Data Mining Basics' },
  { title: 'Tinkle Digest' },
  { title: 'Wings of Fire' }
]
library> db.books.find({ title: /^Data/ }, { _id: 0, title: 1 })
[
  { title: 'Database System Concepts' },
```

```
{ title: 'Data Mining Basics' }  
]
```

(i) \$or takes an array of conditions (OR query). (ii) \$nin = not in the list. (iii) \$exists: false selects documents without the key ({discount: null} would also match these, since null matches a missing key). (iv) A regular expression /^Data/ matches titles beginning with “Data” (type-specific querying).

(Each query 1 M)

e) Data mining vs data warehousing.

4 M




Fig.: Data warehouse feeds data mining

Point	Data mining	Data warehousing
Meaning	Process of extracting hidden patterns / knowledge from large data.	Central repository that stores integrated historical data for analysis.
Nature	An analysis technique (process).	A storage system / database (environment).
Purpose	Prediction and discovery — e.g. which customers may leave.	Reporting and querying — e.g. total sales per region per year.
Techniques / tools	Classification, clustering, association rules, regression.	ETL tools, OLAP, star / snowflake schema, data marts.
Order	Comes after warehousing.	Comes first; supplies cleaned data for mining.

(Any four points, 1 M each)

Q.5

a) 2PL and deadlock.

6 M

Two-Phase Locking: every transaction obtains and releases locks in two phases — a **growing phase** (only acquire locks) followed by a **shrinking phase** (only release locks). The point at which the last lock is acquired is the **lock point**. 2PL ensures conflict serializability (serial order = order of lock points).




Fig.: Two-phase locking — growing and shrinking phases

2PL does not prevent deadlock — example (lock-manager decisions computed by program):

Step	Txn	Operation	Lock manager	Locks held after step	Phase of txn
1	T1	lock-X(A)	granted	T1:X(A)	growing
2	T1	write(A)	—	T1:X(A)	growing
3	T2	lock-X(B)	granted	T1:X(A), T2:X(B)	growing
4	T2	write(B)	—	T1:X(A), T2:X(B)	growing
5	T1	lock-X(B)	WAIT (held by T2:X)	T1:X(A), T2:X(B)	growing
6	T2	lock-S(A)	WAIT (held by T1:X)	T1:X(A), T2:X(B)	growing

Both transactions are still in their growing phase and each waits for the other

T1 holds X(A) and waits for B; T2 holds X(B) and waits for A. Both follow 2PL (no lock has been released), yet neither can proceed — a **deadlock**. The wait-for graph has the cycle T1 → T2 → T1, so the system must roll back one of them (victim) — or use prevention schemes such as wait-die / wound-wait or lock timeouts.




Fig.: Wait-for graph with a cycle (deadlock)

Variants: **strict 2PL** (X-locks held till commit — avoids cascading rollback) and **rigorous 2PL** (all locks till commit). Neither removes deadlocks.

(2PL 2 M, example 3 M, conclusion 1 M)

b) XQuery — join and nested queries.

6 M

Assumed XML data:

```
<customers>
  <customer><cid>C1</cid><cname>Sagar</cname><city>Pune</city></customer>
  <customer><cid>C2</cid><cname>Ayesha</cname><city>Nanded</city></customer>
  <customer><cid>C3</cid><cname>Vikram</cname><city>Latur</city></customer>
</customers>
```

```
<orders>
  <order><oid>01</oid><cid>C1</cid><item>Laptop</item><amount>52000</amount>
</order>
  <order><oid>02</oid><cid>C2</cid><item>Printer</item><amount>9500</amount>
</order>
  <order><oid>03</oid><cid>C1</cid><item>Mouse</item><amount>600</amount>
</order>
  <order><oid>04</oid><cid>C2</cid><item>Router</item><amount>2100</amount>
</order>
</orders>
```

i) Join — customer name, item and amount for orders above 1000:

XQuery:

```
for $c in doc("customers.xml")/customers/customer,
    $o in doc("orders.xml")/orders/order
where $c/cid = $o/cid and xs:decimal($o/amount) > 1000
return <purchase>{ $c/cname, $o/item, $o/amount }</purchase>
```

Output:

```
<purchase>
  <cname>Sagar</cname>
  <item>Laptop</item>
  <amount>52000</amount>
</purchase>
<purchase>
  <cname>Ayesha</cname>
  <item>Printer</item>
  <amount>9500</amount>
</purchase>
<purchase>
  <cname>Ayesha</cname>
  <item>Router</item>
  <amount>2100</amount>
</purchase>
```

ii) Nested query — every customer with all his orders and total amount (a customer with no order appears with an empty list):

XQuery:

```
<report>{
  for $c in doc("customers.xml")/customers/customer
  let $ord := doc("orders.xml")/orders/order[cid = $c/cid]
  return <customer name="{ $c/cname}" total="{ sum($ord/amount) }">{
    for $o in $ord return <item>{ $o/item/text() }</item>
  }</customer>
}</report>
```

Output:

```
<report>
  <customer name="Sagar" total="52600">
    <item>Laptop</item>
    <item>Mouse</item>
  </customer>
  <customer name="Ayesha" total="11600">
    <item>Printer</item>
    <item>Router</item>
  </customer>
  <customer name="Vikram" total="0"/>
</report>
```

In the join, the where clause equates cid of both documents (like an SQL equi-join). The nested query places a FLWOR expression inside the element constructor of the outer FLWOR — like an outer join with grouping.

(Join 3 M, nested query 3 M)

c) Basic operations in MongoDB shell.

6 M

Operation	Syntax
Create / switch database	use <db_name>
Create collection	db.createCollection("name") (or automatically on first insert)
Insert	db.coll.insertOne({...}), db.coll.insertMany([{...}, ...])
Read	db.coll.find(query, projection), findOne()
Update	db.coll.updateOne(filter, {\$set: {...}}), updateMany()
Delete	db.coll.deleteOne(filter), deleteMany(filter)
Drop	db.coll.drop(), db.dropDatabase()

```
test> use hostel
switched to db hostel
hostel> db.createCollection("rooms")
{ ok: 1 }
hostel> db.rooms.insertMany([
  { room: 101, student: "Amit", fees: 30000 },
  { room: 102, student: "Bhavna", fees: 30000 },
  { room: 103, student: "Chetan", fees: 28000 }
])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('6720a1b2c3d4e5f6000000001'),
    '1': ObjectId('6720a1b2c3d4e5f6000000002'),
    '2': ObjectId('6720a1b2c3d4e5f6000000003')
  }
}
hostel> db.rooms.find({ fees: 30000 }, { _id: 0 })
[
  { room: 101, student: 'Amit', fees: 30000 },
  { room: 102, student: 'Bhavna', fees: 30000 }
]
```

```

hostel> db.rooms.updateMany({ fees: 30000 }, { $inc: { fees: 2000 } })
{
  acknowledged: true,
  insertedId: null,
  matchedCount: 2,
  modifiedCount: 2,
  upsertedCount: 0
}
hostel> db.rooms.deleteOne({ room: 103 })
{ acknowledged: true, deletedCount: 1 }
hostel> db.rooms.find({}, { _id: 0 })
[
  { room: 101, student: 'Amit', fees: 32000 },
  { room: 102, student: 'Bhavna', fees: 32000 }
]
hostel> db.rooms.drop()
true
hostel> show collections

```

\$inc increases a numeric field; updateMany() changed 2 documents. After drop() the collection list is empty.

(Each operation with syntax and example 1 M)

Q.6

a) Parallel vs distributed database (six points).

6 M

Point	Parallel database	Distributed database
Location	Processors/disks are in one place (same building / machine room).	Sites are geographically separated (different cities / branches).
Interconnection	Very fast interconnection network (bus, switch, mesh).	Slower network — LAN / WAN / Internet.
Main aim	Performance — higher throughput and lower response time through parallelism.	Data sharing, local autonomy and high availability for users at many sites.
Autonomy	Nodes are not autonomous; whole system works as one DBMS.	Each site has local autonomy and its own local DBMS.
Nodes / software	Usually identical (homogeneous) processors and the same DBMS.	Sites may be heterogeneous (different hardware, OS, DBMS).
Cost of communication	Communication cost is negligible.	Communication cost is high; query plans try to reduce data transfer.
Failure	Failure of the machine room affects the whole system.	Failure of one site does not stop the other sites (replicated data remains available).

(Any six points, 1 M each)

b) Decision-tree classifier; validating a classifier.

A **decision-tree classifier** is a tree in which each **internal node** tests an attribute, each **branch** is an outcome of the test and each **leaf** gives a class label. To classify a new item we start at the root and follow the branches matching its attribute values until a leaf is reached. The tree is built top-down (greedy): at each node the attribute that best separates the classes is chosen — measured by **information gain** (entropy) or Gini index — and the data is partitioned; partitioning stops when a node is pure (one class) or no attributes remain.

Example — predict result of a student (training data, 11 students):

#	Attendance	Assignments	Result
1	high	complete	pass
2	high	complete	pass
3	high	incomplete	pass
4	high	complete	pass
5	low	complete	pass
6	low	incomplete	fail
7	low	incomplete	fail
8	low	complete	pass
9	low	incomplete	fail
10	high	incomplete	pass
11	high	incomplete	pass

Entropy(result) = 0.845; Gain(attendance) = 0.404; Gain(assignments) = 0.300. Attendance has the higher gain, so it is the root test; for low attendance the assignments attribute separates the classes completely. The tree built by the ID3 algorithm (computed by program):




Fig.: Decision tree for predicting result

Validating a classifier: its quality is measured on **test data** not used for training (hold-out) or by **cross-validation** (data divided into k parts; each part is used once for testing). Measures are

computed from the confusion matrix — **accuracy** = $(TP + TN) / \text{total}$, **precision** = $TP / (TP + FP)$, **recall** = $TP / (TP + FN)$.

Test students	Actual	Predicted
high, complete	pass	pass
low, incomplete	fail	fail
high, incomplete	fail	pass
low, complete	pass	pass
low, incomplete	pass	fail
high, complete	pass	pass

With 'pass' as positive: TP = 3, TN = 1, FP = 1, FN = 1; accuracy = $4/6 = 67\%$, precision = $3/4 = 0.75$, recall = $3/4 = 0.75$.

(Explanation 2 M, example tree 2 M, validation 2 M)

c) XPath and XQuery; differences.

6 M

XPath is a language for selecting nodes of an XML document using path expressions (/ child, // descendant, @ attribute, [] predicate, functions such as count()).

Document *library.xml*:

```
<library>
  <book id="B1" year="2019"><title>Database Concepts</title>
  <author>Korth</author><price>850</price></book>
  <book id="B2" year="2021"><title>Learning XML</title><author>Ray</author>
  <price>499</price></book>
  <book id="B3" year="2023"><title>NoSQL Distilled</title>
  <author>Fowler</author><price>620</price></book>
</library>
```

Requirement	XPath expression	Result (executed)
titles of all books	/library/book/title	<title>Database Concepts</title> <title>Learning XML</title> <title>NoSQL Distilled</title>
author of book B2	/library/book[@id="B2"]/author/text()	Ray
titles of books costing less than 700	//book[price < 700]/title	<title>Learning XML</title> <title>NoSQL Distilled</title>

XQuery is the W3C query language for XML (like SQL for tables). It uses XPath to locate nodes and FLWOR expressions to filter, join, sort and construct new XML.

XQuery:

```
for $b in doc("library.xml")/library/book
where xs:integer($b/@year) >= 2020
order by $b/title
return <recent>{ $b/title/text() } ({ string($b/@year) })</recent>
```

Output:

```
<recent>Learning XML (2021)</recent>
<recent>NoSQL Distilled (2023)</recent>
```

Point	XPath	XQuery
Purpose	Language to navigate an XML tree and select nodes.	Full query language to query, join and restructure XML data.
Construct new XML	Cannot create new elements; only selects existing nodes / values.	Can construct new XML elements and documents in the result.
Joins / sorting	No joins between documents; no ordering clause.	Supports joins, nested queries, sorting (order by), grouping.
Relation	XPath 2.0 is a subset of XQuery 1.0.	XQuery is a superset of XPath — like SQL for XML.

(XPath with example 1½ M, XQuery with example 1½ M, four differences 3 M)

Note: This is a **model question paper prepared by Ananda Technologies** only for practice and exam preparation, based on the pattern of previous MSBTE question papers and the K-scheme syllabus. It is **not an official MSBTE paper**, and it does **not** mean that these questions will come in the exam. Answers follow standard textbook points; marks shown are indicative. Free for students — anandatechnologies.in